

Chongqing Polycomp International Corp.

Jianqiao Industiral Park B, Dadukou District Chongqing, China.

Post code: 400082 website: www.cpicfiber.com

Technical support . Tel: (+86-23)68157743 (+86-23)68157178

Marketing Dept. Tel: (+86-23)68157828 (+86-23)681577586

Fax: (+86-23)68157822

Chopped Strand for PBT/PET ECS303N

Identification

Example: ECS303N-3-K

ECS: E-glass Chopped strands

Sizing code: 303N

Chopped length (mm): 3 Filament diameter: 13



Product Description

Special products for PET,PBT, with good color, excellent properties, low fuzz and good fluidity; ECS303N-3-K/HL is used for LDK applications. NPE free.

Product Benefits

- Unique surface treatment technology
- Good dispersion
- Excellent color
- Good operability of process
- Resin bond

Technical Characteristics

Sizing type	Diameter (µm)	Moisture Content (%)	LOI(%)	Bulk Density (g/ cm3)
/	ISO 1888	ISO 3344	ISO 1887	ISO 15100
Silane	±1	≤0.05	□1.25±0.15	0.65±0.15

Product code	Glass Type	Filament diameter[µm]	Chopped length [mm]
ECS303N	ECT	10	3



Chongqing Polycomp International Corp.
Jianqiao Industiral Park B, Dadukou District Chongqing, China. Post code: 400082 website: www.cpicfiber.com Technical support . Tel: (+86-23)68157743 (+86-23)68157178 Marketing Dept. Tel: (+86-23)68157828 (+86-23)681577586 Fax: (+86-23)68157822

Packing

Packing	Weight [kg]	Bag number per pallet	Palletsize [mm] length*width*height
super-sack	1000	1	1140*1140*1100
paper bag	25	40	850*500*120

Pallets illustration



Note: Products can be packed according to the customer's request.

Storage

- If no special requirements, it should be stored in cool and dry place. It is recommended that the temperature control in the 10-30°C, moisture control in 50-75%.
- This product before use should always be placed under the sealed packaging.
- Pallet stacking height should not be more than one layer.





